

## Arco Led

II F0303000 - Steel

Designed by Achille and Pier Giacomo Castiglioni

Floor lamp providing direct light. White Carrara marble base. Satin-finish stainless steel telescopic stem. Pressed, polished and zapon-varnished aluminum swiveling and height-adjustable reflector.




### Main specifications


|                                 |                                                       |                           |         |
|---------------------------------|-------------------------------------------------------|---------------------------|---------|
| <b>Mounting Environment</b>     | Floor<br>Indoor dry location                          | <b>Lamp holder</b>        | COB LED |
| <b>Light source type</b>        | LED                                                   | <b>Dimmable</b>           | Yes     |
| <b>Light source replaceable</b> | Replaceable (LED only) light source by a professional | <b>Autoprotected Lamp</b> | No      |
| <b>LED type</b>                 | LED array                                             | <b>Number of heads</b>    | 1       |
| <b>System Flux (lm)</b>         | 1224                                                  | <b>Source Power (W)</b>   | 28      |

### Optical

|                              |            |
|------------------------------|------------|
| <b>Lighting Type</b>         | Direct     |
| <b>Lighting distribution</b> | Asymmetric |
| <b>CCT (K)</b>               | 2700       |
| <b>Cold Beam Lighting</b>    | No         |
| <b>Extreme Cut off</b>       | No         |



Luminous flux luminaire  
1224 lm



### Electrical

|                           |                 |                                 |                                         |
|---------------------------|-----------------|---------------------------------|-----------------------------------------|
| <b>Insulation class</b>   | III             | <b>Dimmable type</b>            | Electronic 12V                          |
| <b>Frequency (Hz)</b>     | 50/60           | <b>Batteries Inside</b>         | No                                      |
| <b>Main Voltage (Vac)</b> | 100-240/48      | <b>Dimming Interface</b>        | Dimmer                                  |
| <b>Driver</b>             | Remote included | <b>Power supply replaceable</b> | Integrated                              |
| <b>Dimmable</b>           | Yes             | <b>Cord length (mm)</b>         | Replaceable control gear by an end-user |
|                           |                 |                                 | 2700                                    |

|                          |                        |
|--------------------------|------------------------|
| <b>Plug Type</b>         | Type G, Type A, Type C |
| <b>Charging Min Time</b> | No                     |

### Physical

|                          |        |
|--------------------------|--------|
| <b>Colour</b>            | Steel  |
| <b>Net weight (kg)</b>   | 63.85  |
| <b>Gross weight (kg)</b> | 140.79 |
| <b>IP</b>                | 20     |
| <b>IP external</b>       | 20     |

